



Designation	Dimensions				Mounting dimensions				Weight (kg)
	d	D	B	r min	da min	Da max	ra max		
SS135	5	19	6	0.3	7	17	0.3	0.009	
SS126	6	19	6	0.3	8	17	0.3	0.009	
SS127	7	22	7	0.3	9	20	0.3	0.014	
SS108	8	22	7	0.3	10	20	0.3	0.014	
SS129	9	26	8	0.6	13	22	0.6	0.022	
SS1200	10	30	9	0.6	14	26	0.6	0.034	
SS2200	10	30	14	0.6	14	26	0.6	0.047	
SS1300	10	25	11	0.6	14	31	0.6	0.058	
SS2300	10	25	17	0.6	14	31	0.6	0.085	
SS1201	12	32	10	0.6	16	28	0.6	0.04	
SS2201	12	32	14	0.6	16	28	0.6	0.053	
SS1301	12	37	12	1	17	32	1	0.067	
SS2301	12	37	17	1	17	32	1	0.095	
SS1202	15	35	11	0.6	19	31	0.6	0.049	
SS2202	15	35	14	0.6	19	31	0.6	0.06	
SS1302	15	42	13	1	20	37	1	0.094	
SS2302	15	42	17	1	20	37	1	0.11	
SS1203	17	40	12	0.6	21	36	0.6	0.073	
SS2203	17	40	16	0.6	21	36	0.6	0.088	
SS1303	17	47	14	1	22	42	1	0.13	
SS2303	17	47	19	1	22	42	1	0.16	
SS1204	20	47	14	1	25	42	1	0.12	
SS2204	20	47	18	1	25	42	1	0.14	
SS1304	20	52	15	1.1	26.5	45.5	1	0.16	
SS1304	20	52	21	1.1	26.5	45.5	1	0.21	
SS1205	25	52	15	1	30	47	1	0.14	
SS2205	25	52	18	1	30	47	1	0.16	
SS1305	25	62	17	1.1	31.5	55.5	1	0.26	
SS2305	25	62	24	1.1	31.5	55.5	1	0.34	
SS1206	30	62	16	1	35	57	1	0.22	
SS2206	30	62	20	1	35	57	1	0.26	
SS1306	30	72	19	1.1	36.5	65.5	1	0.39	
SS2306	30	72	27	1.1	36.5	65.5	1	0.5	
SS1207	35	72	17	1.1	41.5	65.5	1	0.32	
SS2207	35	72	23	1.1	41.5	65.5	1	0.4	
SS1307	35	80	21	1.5	43	72	1.5	0.51	
SS2307	35	80	31	1.5	43	72	1.5	0.68	
SS1208	40	80	18	1.1	46.5	73.5	1	0.42	
SS2208	40	80	23	1.1	46.5	73.5	1	0.51	
SS1308	40	90	23	1.5	48	82	1.5	0.72	
SS2308	40	90	33	1.5	48	82	1.5	0.93	
SS1209	45	85	19	1.1	51.5	78.5	1	0.47	
SS2209	45	85	23	1.1	51.5	78.5	1	0.55	
SS1309	45	100	25	1.5	53	92	1.5	0.96	
SS2309	45	100	36	1.5	53	92	1.5	1.23	
SS1210	50	90	20	1.1	56.5	83.5	1	0.53	
SS2210	50	90	23	1.1	56.5	83.5	1	0.59	
SS1310	50	110	27	2	59	101	2	1.21	
SS2310	50	110	40	2	59	101	2	1.64	
SS1211	55	100	21	1.5	63	92	1.5	0.71	
SS2211	55	100	25	1.5	63	92	1.5	0.81	
SS1311	55	120	29	2	64	111	2	1.58	
SS2311	55	120	43	2	64	111	2	2.1	
SS1212	60	110	22	1.5	68	102	1.5	0.9	
SS2212	60	110	28	1.5	68	102	1.5	1.09	
SS1312	60	130	31	2.1	71	119	2	1.96	
SS2312	60	130	46	2.1	71	119	2	2.6	
SS1213	65	120	23	1.5	73	112	1.5	1.15	
SS2213	65	120	31	1.5	73	112	1.5	1.46	
SS1313	65	140	33	2.1	76	129	2	2.45	
SS2313	65	140	48	2.1	76	129	2	3.23	
SS1214	70	125	24	1.5	78	117	1.5	1.26	
SS2214	70	125	31	1.5	78	117	1.5	1.52	
SS1314	70	150	35	2.1	81	139	2	2.99	
SS2314	70	150	51	2.1	81	139	2	4.23	
SS1215	75	130	25	1.5	83	122	1.5	1.36	
SS2215	75	130	31	1.5	83	122	1.5	1.62	
SS1216	80	140	26	2	89	131	2	1.67	
SS2216	80	140	33	2	89	131	2	2.04	

SS1217	85	150	28	2	94	141	2	2.07
SS2217	85	150	36	2	94	141	2	2.52