



Name	(D) Roller O.D.	(B) Roller Width	(A) Stud Dia.	(M) Stud Length	Basic Dynamic Rating (lbs)
CR-1/2-XB-SS	0.5	0.375	0.19	5/8	475
CR-5/8-XB-SS	0.625	0.4375	0.25	3/4	695
CR-3/4-XB-SS	0.75	0.5	0.375	7/8	1,245
CR-7/8-XB-SS	0.875	0.5	0.375	3/4	1,245
CR-1-XB-SS	1	0.625	0.4375	1	1,560
CR-1-1/8-XB-SS	1.125	0.625	0.4375	1	1,560
CR-1-1/4-XB-SS	1.25	0.75	0.5	1-1/4	2,750
CR-1-3/8-XB-SS	1.375	0.75	0.5	1-1/4	2,750
CR-1-1/2-XB-SS	1.5	0.875	0.625	1-1/2	3,390

CR-1-5/8-XB-SS	1.625	0.875	0.625	1-1/2	3,390
CR-1-3/4-XB-SS	1.75	1	0.75	1-3/4	4,470
CR-1-7/8-XB-SS	1.875	1	0.75	1-3/4	4,470
CR-2-XB-SS	2	1.25	0.875	2	5,660
CR-2-1/4-XB-SS	2.25	1.25	0.875	2	5,660
CR-2-1/2-XB-SS	2.5	1.5	1	2-1/4	7,959
CR-2-3/4-XB-SS	2.75	1.5	1	2-1/4	7,959
CR-3-XB-SS	3	1.75	1.25	2-1/2	10,486